

SPECIFICATIONS

Model/Width	Transport Dimensions	Approx. Weight
TF 1-14	14'0" W Rigid	2,250 lb.
TF 1-18	18'0" W Rigid	2,925 lb.
TF 1-19	19'0" W Rigid	3,000 lb.
TF 1-20	20'0" W Rigid	3,225 lb.
TF 1-23	23'0" W Rigid	3,675 lb.
TF 1-25	25'0" W Rigid	3,950 lb.
TF 3-22	14'2" W x 8'2" H	4,400 lb.
TF 3-26	14'2" W x 10'0" H	5,075 lb.
TF 3-28	14'2" W x 10'6" H	5,200 lb.
TF 3-29	16'6" W x 11'6" H	5,800 lb.
TF 3-33	16'6" W x 13'2" H	6,475 lb.
TF 3-35	16'6" W x 14'0" H	7,000 lb.
TF 3-34	17'6" W x 13'6" H	6,600 lb.
TF 3-38	17'6" W x 15'2" H	7,275 lb.
TF 3-36	19'0" W x 13'6" H	7,200 lb.
TF 3-40	19'0" W x 15'2" H	7,875 lb.
TF 5-42	18'9" W x 13'9" H	8,400 lb.
TF 5-46	18'9" W x 13'9" H	9,075 lb.
TF 5-48	18'9" W x 13'9" H	9,600 lb.
TF 5-50	18'9" W x 13'9" H	10,275 lb.
TF 5-52	20'8" W x 13'9" H	11,400 lb.
TF 5-56	20'8" W x 14'0" H	11,675 lb.